

MAKE EVERY TRIP A SAFE TRIP

TATA LP 909



4920mm
Long Wheelbase



Ergonomic
Driver Seating Position



Best In Class
Fuel Efficiency



(37+D)*
Seating Capacity



Anti-roll Bar on Front & Rear Axle
for Better Vehicle Stability

*BRTA approved



LP 909 BUS SPECIFICATIONS

MODEL

TATA 497 TCIC

TYPE

Turbo charged, Intercooled, Diesel Engine

CYLINDERS / DISPLACEMENT

4 Cylinder / 3783 cc

MAX. OUTPUT

90 Ps @ 2400 rpm

MAX. TORQUE

325 Nm @ 1300-1600rpm

CLUTCH

Single Plate Dry Friction 280 mm Dia.

STEERING SYSTEM

Power Steering

GEARBOX

5 Speed Synchromesh

BRAKES

Dual Circuit Full Air S-cam

SUSPENSION

Semi elliptical Leaf Spring with Hydraulic Double Acting Telescopic Shock Absorber at both Front and Rear

TYRES

8.25 x 16 16PR

WHEELBASE

4920 mm

CHASSIS WIDTH

2140 mm

CHASSIS LENGTH

8895 mm

MIN. TURNING RADIUS

8.75m

GROUND CLEARANCE

210 mm

GVW

9000 kg

MAX. SPEED

98 KMPH

GRADEABILITY

21.80%

BRTA APPROVED SEATING CAPACITY

37 + D

ALTERNATOR

12 V - 65 Amp

BATTERY

12 V - 150 Ah